

Application No. 10/824,205  
Response dated January 4, 2005  
Reply to Office Action of December 9, 2004

**IN THE CLAIMS:**

1. (currently amended) An electric motor, comprising:
  - (a) a stator having a circular magnetic conductor wherein an even number of permanent magnets are attached at a uniform pitch;
  - (b) a rotor, ~~the rotor being~~ separated from the stator by an air gap and carrying a plurality of electromagnets interacting with the permanent magnets in the stator;
  - (c) a distributing collector, ~~the collector being~~ attached to the stator and having a plurality of current conductor plates located around the collector's circumference, the plurality of current conductor plates ~~being~~ separated by dielectric gaps and further ~~being~~ electrically connected at alternating polarity to a direct current supply;
  - (d) a plurality of brushes attached to the rotor, at least two of the brushes ~~being~~ electrically connected with at least two of the collector plates and each brush ~~being~~ electrically connected to at least two of the electromagnet coil windings, wherein the coil windings of adjacent electromagnets are electrically connected in pairs and in series aiding, and the windings of the coils of a pair of diametrically opposite electromagnets in series opposing;
  - (e) capacitors ~~being~~ electrically connected to the leads of the electromagnet coil windings electrically connected to the brushes thereby forming a plurality of resonant circuits;
  - (f) wherein the number (n) of the permanent magnets of the stator and the number (m) of the resonant circuits ~~being is~~ determined from the equations  $n=10+4k$ ,  $m=2+k$ , where k is a whole number; and
  - (g) wherein the number of plates in the distributing collector ~~being is~~ equal to the number of permanent magnets in the stator, and the axial lines of the dielectric gaps in the distributing collector ~~being are~~ aligned along the axial lines of the permanent magnets of the stator.
2. (original) The electric motor of claim 1, wherein the number of loops in the coil

Application No. 10/824,205  
Response dated January 4, 2005  
Reply to Office Action of December 9, 2004

windings of diametrically opposite electromagnets is different, the difference being selected from set of ratios consisting of  $1/32$ ,  $1/16$ ,  $1/8$ , and  $1/4$ .

3. (original) The electric motor of claim 1, wherein the rating of at least one of the capacitors electrically connected to the electromagnet coil windings is proportional to the total number of loops in these windings.

4. (original) The electric motor of claim 2, wherein the rating of at least one of the capacitors electrically connected to the electromagnet coil windings is proportional to the total number of loops in these windings.

5. (original) The electric motor of claim 1, wherein the rotor is located outside of the stator.

6. (original) The electric motor of claim 2, wherein the rotor is located outside of the stator.

7. (original) The electric motor of claim 3, wherein the rotor is located outside of the stator.

8. (original) The electric motor of claim 4, wherein the rotor is located outside of the stator.

9. (original) The electric motor of claim 1, wherein the rotor is located inside of the stator.

10. (original) The electric motor of claim 2, wherein the rotor is located inside of the stator.

11. (original) The electric motor of claim 3, wherein the rotor is located inside of the stator.

12. (original) The electric motor of claim 4, wherein the rotor is located inside of the stator.

13. (original) The electric motor of claim 1, wherein the brushes are adjustable in a

Application No. 10/824,205  
Response dated January 4, 2005  
Reply to Office Action of December 9, 2004

position on the circumference relative to the collector.

14. (original) The electric motor of claim 2, wherein the brushes are adjustable relative to the collector plates.

15. (original) The electric motor of claim 3, wherein the brushes are adjustable relative to the collector plates.

16. (original) The electric motor of claim 4, wherein the brushes are adjustable relative to the collector plates.

17. (original) The electric motor of claim 5, wherein the brushes are adjustable relative to the collector plates.

18. (original) The electric motor of claim 6, wherein the brushes are adjustable relative to the collector plates.

19. (original) The electric motor of claim 9, wherein the brushes are adjustable relative to the collector plates.

20. (original) The electric motor of claim 10, wherein the brushes are adjustable relative to the collector plates.

Application No. 10/824,205  
Response dated January 4, 2005  
Reply to Office Action of December 9, 2004

**SUMMARY:**

The Examiner noted that the applicant had not filed a certified copy of the Russian application. In this response, applicant has submitted the certified copy of the Russian priority document.

In the office action, the Examiner objected to the leader line for reference numeral "2" in Figure 1. Applicant has amended Figure 1 to have the leader line point to the stator. The substitute sheet "1/3" is included. Also included is a copy of sheet "1/3" where the change has been circled.

The Examiner objected to various portions of the Specification. Applicant has made amendments to the Specification to address these objections.

The Examiner made various formality objections to claim 1. The applicant has amended claim 1 to address these objections.

The Examiner objected to page 1 of the Specification for including the attorney docket number, inventor, and assignee information. Applicant has amended the Specification to delete these items.